

WHAT IS CLAIMED IS:

1. A thermally-assisted magnetic recording head capable of recording information magnetically on a recording medium, comprising:

a laser device configured to emit a light to heat the recording medium to reduce magnetic coercive force thereof;

a light absorbing film provided between the laser device and the recording medium, the light absorbing film having an aperture through which the light is applied to the recording medium; and

a magnetic pole configured to record the information magnetically on the recording medium by applying recording magnetic field to the recording medium having the reduced coercive force,

the aperture being adapted so that a polarizing direction of the light emitted from the laser device is approximately perpendicular to a direction along a longitudinal extension of recording tracks formed on the recording medium, and

a width W1 of the aperture taken along the polarizing direction being smaller than a width W2 of the aperture taken approximately perpendicular to the polarizing direction.

2. The thermally-assisted magnetic recording head according to claim 1, wherein the width W1 is shorter than $1/2$ of a wavelength at the center of a spectrum of the light emitted from the laser device.

3. The thermally-assisted magnetic head according to claim 1, further comprising a dielectric film provided between the laser device and the light absorbing film.

4. The thermally-assisted magnetic head according to claim 3, wherein an optical film thickness of the dielectric film is in a range from 0.05λ to 0.35λ relative to the wavelength λ of the light emitted from the laser device.

5. The thermally-assisted magnetic recording head according to claim 1, wherein the width W_1 is within a range in which an absorption loss through the aperture of light having an electric field vector perpendicular to the direction of the aperture width W_1 is 10 times as much as an absorption loss through the aperture of light having a magnetic field vector perpendicular to the direction of the aperture width W_1 , or even higher.

6. The thermally-assisted magnetic recording head according to claim 1, wherein the laser device is a semiconductor laser device of which laser oscillation mode is a TM mode.

7. The thermally-assisted magnetic recording head according to claim 1, further comprising an optical light collector which converges the light emitted from the laser device to direct it into the aperture.

8. The thermally-assisted magnetic recording head according to claim 1, wherein the aperture is filled with dielectric or semiconductor material.

9. The thermally-assisted magnetic recording head according to claim 1, further comprising a reproducing device configured to reproduce the information recorded on the recording medium.

10. A thermally-assisted magnetic recording apparatus capable of recording information magnetically on a recording medium, comprising:

- a thermally-assisted magnetic recording head; and
- an actuating mechanism configured to move recording medium and the magnetic recording head relative to each other,

wherein the thermally-assisted magnetic recording head includes

- a laser device configured to emit a light to heat the recording medium to reduce magnetic coercive force thereof;
- a light absorbing film provided between the laser device

and the recording medium, the light absorbing film having an aperture through which the light is applied to the recording medium; and

a magnetic pole configured to record the information magnetically on the recording medium by applying recording magnetic field to the recording medium having the reduced coercive force,

the aperture being adapted so that a polarizing direction of the light emitted from the laser device is approximately perpendicular to a direction along a longitudinal extension of recording tracks formed on the recording medium, and

a width of the aperture taken along the polarizing direction being smaller than a width of the aperture taken approximately perpendicular to the polarizing direction.

11. The thermally-assisted magnetic apparatus according to claim 10, further comprising a recording medium,

the recording medium including a record layer in which magnetic information is recorded, and an antireflection layer made of dielectric or semiconductor material deposited over the record layer.

12. A thermally-assisted magnetic recording head capable of recording information magnetically on a recording medium, comprising:

a heating source configured to irradiate the recording medium with a heat beam to reduce magnetic coercive force of the recording medium; and

a magnetic pole configured to apply recording magnetic field to the recording medium having the reduced coercive force,

a radiating portion emitting the heat beam of the heating source being in a receding position from a tip of the magnetic pole when seen from the recording medium, and the tip of the magnetic pole protruding between the heating source and the recording medium.

13. The thermally-assisted magnetic recording head

0977394 0440

the material transparent to light having a distribution uneven thickness so that a tip of the magnetic pole protrudes between the heating device and the recording medium.

applying a material transparent to light in a path in the heating device, the material transparent to light being over either the first substrate or the second substrate, and the heat beam being emitted through the path, and

the material transparent to light having a distribution uneven thickness so that a tip of the magnetic pole protrudes between the heating device and the recording medium.

fabricating the heating device on a first substrate,
fabricating the magnetic pole on a second substrate, with
its tip being directed upward, and

connecting the heating device and the magnetic pole with the first substrate and the second substrate being opposed to each other, so that the tip of the magnetic pole protrudes between the heating device and the recording medium.